



# Surface RDL EMILLIA REFLECTOR PRO




## INTENDED USE

Hi-BEAM EMILLIA LED round surface downlight comes with reflector. Deliver excellent led performance for applications such as office, meeting room, classroom, house or hotel to replace conventional PLC downlight.


## CONSTRUCTION AND OPTICS

Powder coated metal housing with plastic diffuser come with clear diffuser. Housing colour in white and black. Color temperature available in 3000K, 4000K and 6500K.

## DIMENSIONS



## LINE DRAWING



## DIMENSION OF FITTING

Pro Series, Philips Driver

Product Code	Model Code	Wattage	Lumens	Color Temperature	Φ mm	H mm
EWPROSR-15W	EW15	15W	1200lm	3000K,4000K,6500K	110	125
EWPROSR-20W	EW20	20W	1600lm	3000K,4000K,6500K	130	153
EWPROSR-30W	EW30	30W	2400lm	3000K,4000K,6500K	170	183
EWPROSR-40W	EW40	40W	3200lm	3000K,4000K,6500K	195	195

\*\*Please refer to driver data sheet for the circuit looping details for the MCB / Circuit Breaker you use for your installation.

# PHILIPS

Specifications and dimension subject to change without notice



**HBL**<sup>®</sup>  
HI-BEAM™ Lighting