

Luxtron STLA222 GEN 2












DIMENSIONS



DIMENSION OF FITTING

Model	Wattage	Lumens	Weight kg	Replacement
STLA222G2090-40	92W	12880 lm	5.32	SON 250W
STLA222G2090-57	92W	12880 lm	5.32	SON 250W
STLA222G2120-40	119W	16660 lm	5.33	SON 250W
STLA222G2120-57	119W	16660 lm	5.33	SON 250W
STLA222G2140-40	141W	19740 lm	5.33	SON 250W/400W
STLA222G2140-57	141W	19740 lm	5.33	SON 250W/400W

INTENDED USE


The STLA222 Series LED luminaire provides uncompromising optical performance and outstanding versatility for a wide variety of area and compound lighting applications. Luxtron high power SMT LED engine technology delivers reliable uniform and energy-conscious illumination to walkways, parking lots, commercial and garden.

CONSTRUCTION AND OPTICS

Heavy-duty cast aluminum housing with polyester powder coat paint for superior protection against fade and wear. Offered standard in 4000K & 5700K (+/- 275K) CCT and nominal 70 CRI.

LED drivers hard mounted to die-cast aluminum back casting for optimal heat sinking and operation efficiency. Thermal management incorporates both conduction and natural convection to transfer heat rapidly away from the LED source and retain optimal efficiency and light output.

LINE DRAWING



ORDERING INFORMATION

Lead times will vary based on options selected. Consult with your sales representative. Example: STLA222G2090-40

Туре	Color Fitting	LED	Wattage	сстк
Streetlight STLA222	B Blue W White G Dark Grey	(blank) 2	090 92w 120 119w 140 141w	-30 3000K -40 4000K -57 5700K





Carton: Dimension and Weight

Model	Standard Pack	Length (cm) per ctn	Width (cm) per ctn	Height (cm) per ctn	Gross Weight (kg/ctn)	Net Weight (kg/pc)
STLA222G2090-40	1pc/ctn	77	31	15	5.98	5.32
STLA222G2090-57	1pc/ctn	77	31	15	5.98	5.32
STLA222G2120-40	1pc/ctn	77	31	15	5.99	5.33
STLA222G2120-57	1pc/ctn	77	31	15	5.99	5.33
STLA222G2140-40	1pc/ctn	77	31	15	5.99	5.33
STLA222G2140-57	1pc/ctn	77	31	15	5.99	5.33



