



# Recess RDL Apollo Pro



## INTENDED USE


Apollo round recessed LED downlights great for retrofit and new construction applications. Optimal for commercial application such as office, hall, hotel or shopping mall or villa. LED lifespan of 50,000 hours.

## CONSTRUCTION AND OPTICS


Round recessed LED downlight with aluminium die casting housing, mirror reflector and clear glass diffuser. It come with high efficient black aluminium die casting heat sink.

The working temperature in -20°C - +35°C. The input voltage power of AC210-280V/50-60HZ.

## DIMENSIONS



## LINE DRAWING



## DIMENSION OF FITTING

Product Code	Model Code	Wattage	Lumens	Color Temperature	H mm	Φ mm	Ø mm	CRI
RRDLAPO-30	RRDLAPO-30	30W	3900lm	3000-4000K	95	200	170	80
RRDLAPO-38	RRDLAPO-38	38W	4900lm	3000-4000K	110	230	210	80
RRDLAPO-42	RRDLAPO-42	42W	5550lm	3000-4000K	110	230	210	80

\*\*Please refer to driver data sheet for the circuit looping details for the MCB / Circuit Breaker you use for your installation.



## APOLLO 38W ROUND RECESS DOWNLIGHT

Apollo 38W round recessed LED downlights great for retrofit and new construction applications. Optimal for commercial application such as oce, hall, hotel or shopping mall or villa. LED lifespan of 50,000 hours.




### Product data

#### General Information

Product family code	RRDLAPO-38
Housing Material	Aluminum Diecasting Housing , Anti-Reflector & Anti- Glare Screen Internal Reflector, Shatterproof Clear Glass Diffuser
Housing Color	White
Color Temperature	3000-4000K
CRI	80 >
IP	IP54
IK	IK08
MacAdams	3
LED Light Source	CREE
LED Life Span	50,000hrs
Operating Temperature	-20C to +35C
Classification	Class 1
Power Supply	210VAC-280VAC 50/60 Hz
Initial Input Power	38W
Total Luminous Flux	4900lm
Power Factor	>0. 95

#### Photometric

120°



#### Dimension

Dimension: (Dia)230 mm x (H)110mm  
Cutout 210mm





## APOLLO 42W ROUND RECESS DOWNLIGHT

Apollo 42W round recessed LED downlights great for retrofit and new construction applications. Optimal for commercial application such as oce, hall, hotel or shopping mall or villa. LED lifespan of 50,000 hours.




### Product data

#### General Information

Product family code	RRDLAPO-42
Housing Material	Aluminum Diecasting Housing , Anti-Reflector & Anti- Glare Screen Internal Reflector, Shatterproof Clear Glass Diffuser
Housing Color	White
Color Temperature	3000-4000K
CRI	80 >
IP	IP54
IK	IK08
MacAdams	3
LED Light Source	CREE
LED Life Span	50,000hrs
Operating Temperature	-20C to +35C
Classification	Class 1
Power Supply	210VAC-280VAC 50/60 Hz

#### Photometric

120°



#### Dimension

Dimension: (Dia)230 mm x (H)110mm  
Cutout 210mm



Note: Specification are subject to change without prior notice



HI-BEAM™ Lighting





## APOLLO 30W ROUND RECESS DOWNLIGHT

Apollo 30W round recessed LED downlights great for retrofit and new construction applications. Optimal for commercial application such as oce, hall, hotel or shopping mall or villa. LED lifespan of 50,000 hours.



### Product data

#### General Information


Product family code	RRDLAPO-30
Housing Material	Aluminum Diecasting Housing , Anti-Reflector & Anti- Glare Screen Internal Reflector, Shatterproof Clear Glass Diffuser
Housing Color	White
Color Temperature	3000-4000K
CRI	80 >
IP	IP54
IK	IK08
MacAdams	3
LED Light Source	CREE

LED Life Span	50,000hrs
Operating Temperature	-20C to +35C
Classification	Class 1
Power Supply	210VAC-280VAC 50/60 Hz

Initial Input Power	30W
Total Luminous Flu	3900 lm
Power Factor	>0. 95

#### Photometric

120°



#### Dimension

Dimension: (Dia)200 mm x (H)95 mm  
Cutout : 170 mm



Note: Specification are subject to change without prior notice



HI-BEAM™ Lighting

